



# ORDERING CODES FOR PRESSURE GAUGES

<b>Pressure gauges dimension</b>	
04	Ø 40 mm
05	Ø 50 mm
06	Ø 63 mm
07	72x72 mm
08	Ø 80 mm
09	96x96 mm
10	Ø 100 mm
14	144x72 mm
16	Ø 160 mm
<b>Materials</b>	
1	Dry RST / bajonet Acryl Capsule
2	Dry Black steel Acryl Bourdon tube
3	Dry RST / pressed Acryl Bourdon tube
4	Dry RST / bajonet Acryl Bourdon tube
6	Filled RST / bajonet Glass Capsule
7	Filled RST / pressed Glass Bourdon tube
8	Filled RST / bajonet Glass Bourdon tube
<b>Connection</b>	
0	Radial
1	Axial
<b>Wetted parts</b>	
1	Brass
2	SS 316
<b>Scale</b>	
A	mbar
B	bar
C	psi
D	Special scale
T	Accuracy 0,6%
<b>Ranges</b>	
A	-1 - 0
B	-1 - 1.5
C	-1 - 3
D	-1 - 5
E	-1 - 9
F	-1 - 15
G	0 - 0.6
H	0 - 1
I	0 - 1.6
J	0 - 2.5
K	0 - 4
L	0 - 6
M	0 - 10
N	0 - 16
O	0 - 25
P	0 - 40
Q	0 - 60
R	0 - 100
S	0 - 160
T	0 - 250
U	0 - 315
V	0 - 400
X	0 - 600
Y	0 - 1000
<b>Other</b>	
V	Vacuum

10 - Diameter Ø100 mm  
 8 - With filling liquid glyserine  
 1 - Connection G1/2 axial  
 2 - Material AISI-316  
 B - Scale in bar  
 K - Range 0...4

Lyth-Instrument Oy  
 Peltosaarenkatu 8  
 FI-11130 Riihimäki  
 Finland , Europe

phone: + 358-19-760330  
 fax : + 358-19-722085  
[www.lyth.fi](http://www.lyth.fi)