



PRESSURE GAUGES STAINLESS STEEL HEAVY VERSIONS GLYSERINE FILLED



Case:
Stainless steel W 1.4301

Glass:
Safety glass

Movement:
Stainless steel W 1.4571

Accuracy:
Ø 63 +/- 1,6 %
Ø 100 +/- 1,0 %
Ø 160 +/- 1,0 %

Measuring system:
Bourdon-tube
Stainless steel W 1.4571

Max. process temperature:
60 °C

Code	Type	Diam.	Ranges	Connect	Materials
06702-BA	702	63	-1 - 0 bar	G1/4 Radial	SS / SS
06702-BH	702	63	0 - 1 bar	G1/4 Radial	SS / SS
06702-BJ	702	63	0 - 2,5 bar	G1/4 Radial	SS / SS
06702-BK	702	63	0 - 4 bar	G1/4 Radial	SS / SS
06702-BL	702	63	0 - 6 bar	G1/4 Radial	SS / SS
06702-BM	702	63	0 - 10 bar	G1/4 Radial	SS / SS
06702-BN	702	63	0 - 16 bar	G1/4 Radial	SS / SS
06702-BO	702	63	0 - 25 bar	G1/4 Radial	SS / SS
06702-BP	702	63	0 - 40 bar	G1/4 Radial	SS / SS
06702-BQ	702	63	0 - 60 bar	G1/4 Radial	SS / SS
10802-BA	802	100	-1 - 0 bar	G1/2 Radial	SS / SS
10802-BB	802	100	-1 - 1,5 bar	G1/2 Radial	SS / SS
10802-BC	802	100	-1 - 3 bar	G1/2 Radial	SS / SS
10802-BD	802	100	-1 - 5 bar	G1/2 Radial	SS / SS
10802-BE	802	100	-1 - 9 bar	G1/2 Radial	SS / SS
10802-BF	802	100	-1 - 15 bar	G1/2 Radial	SS / SS
10802-BG	802	100	0 - 0,6 bar	G1/2 Radial	SS / SS
10802-BH	802	100	0 - 1 bar	G1/2 Radial	SS / SS
10802-BI	802	100	0 - 1,6 bar	G1/2 Radial	SS / SS
10802-BJ	802	100	0 - 2,5 bar	G1/2 Radial	SS / SS
10802-BK	802	100	0 - 4 bar	G1/2 Radial	SS / SS
10802-BL	802	100	0 - 6 bar	G1/2 Radial	SS / SS
10802-BM	802	100	0 - 10 bar	G1/2 Radial	SS / SS
10802-BN	802	100	0 - 16 bar	G1/2 Radial	SS / SS
10802-BO	802	100	0 - 25 bar	G1/2 Radial	SS / SS
10802-BP	802	100	0 - 40 bar	G1/2 Radial	SS / SS
10802-BQ	802	100	0 - 60 bar	G1/2 Radial	SS / SS
10802-BR	802	100	0 - 100 bar	G1/2 Radial	SS / SS
10802-BS	802	100	0 - 160 bar	G1/2 Radial	SS / SS
10802-BT	802	100	0 - 250 bar	G1/2 Radial	SS / SS
10802-BU	802	100	0 - 315 bar	G1/2 Radial	SS / SS
10802-BV	802	100	0 - 400 bar	G1/2 Radial	SS / SS
10802-BX	802	100	0 - 600 bar	G1/2 Radial	SS / SS

Lyth-Instrument Oy
Peltosaarekatu 8
FI-11130 Riihimäki
Finland , Europe

phone: + 358-19-760330
fax : + 358-19-722085
www.lyth.fi



PRESSURE GAUGES STAINLESS STEEL HEAVY VERSIONS GLYSERINE FILLED



Case:
Stainless steel W 1.4301

Glass:
Safety glass

Movement:
Stainless steel W 1.4571

Accuracy:
Ø 63 +/- 1,6 %
Ø 100 +/- 1,0 %
Ø 160 +/- 1,0 %

Measuring system:
Bourdon-tube
Stainless steel W 1.4571

Max. process temperature:
60 °C

Code	Type	Diam.	Ranges	Connect	Materials
10812-BA	812	100	-1 - 0 bar	G1/2 Axial	SS / SS
10812-BB	812	100	-1 - 1,5 bar	G1/2 Axial	SS / SS
10812-BC	812	100	-1 - 3 bar	G1/2 Axial	SS / SS
10812-BD	812	100	-1 - 5 bar	G1/2 Axial	SS / SS
10812-BE	812	100	-1 - 9 bar	G1/2 Axial	SS / SS
10812-BF	812	100	-1 - 15 bar	G1/2 Axial	SS / SS
10812-BH	812	100	0 - 1 bar	G1/2 Axial	SS / SS
10812-BJ	812	100	0 - 2,5 bar	G1/2 Axial	SS / SS
10812-BK	812	100	0 - 4 bar	G1/2 Axial	SS / SS
10812-BL	812	100	0 - 6 bar	G1/2 Axial	SS / SS
10812-BM	812	100	0 - 10 bar	G1/2 Axial	SS / SS
10812-BN	812	100	0 - 16 bar	G1/2 Axial	SS / SS
10812-BO	812	100	0 - 25 bar	G1/2 Axial	SS / SS
10812-BP	812	100	0 - 40 bar	G1/2 Axial	SS / SS
10812-BQ	812	100	0 - 60 bar	G1/2 Axial	SS / SS
10812-BR	812	100	0 - 100 bar	G1/2 Axial	SS / SS
10812-BT	812	100	0 - 250 bar	G1/2 Axial	SS / SS
10812-BV	812	100	0 - 400 bar	G1/2 Axial	SS / SS
10812-BX	812	100	0 - 600 bar	G1/2 Axial	SS / SS
16802-BA	802	160	-1 - 0 bar	G1/2 Radial	SS / SS
16802-BC	802	160	-1 - 3 bar	G1/2 Radial	SS / SS
16802-BD	802	160	-1 - 5 bar	G1/2 Radial	SS / SS
16802-BE	802	160	-1 - 9 bar	G1/2 Radial	SS / SS
16802-BF	802	160	-1 - 15 bar	G1/2 Radial	SS / SS
16802-BH	802	160	0 - 1 bar	G1/2 Radial	SS / SS
16802-BK	802	160	0 - 4 bar	G1/2 Radial	SS / SS
16802-BL	802	160	0 - 6 bar	G1/2 Radial	SS / SS
16802-BM	802	160	0 - 10 bar	G1/2 Radial	SS / SS
16802-BN	802	160	0 - 16 bar	G1/2 Radial	SS / SS
16802-BO	802	160	0 - 25 bar	G1/2 Radial	SS / SS
16802-BP	802	160	0 - 40 bar	G1/2 Radial	SS / SS
16802-BQ	802	160	0 - 60 bar	G1/2 Radial	SS / SS
16802-BR	802	160	0 - 100 bar	G1/2 Radial	SS / SS
16802-BS	802	160	0 - 160 bar	G1/2 Radial	SS / SS
16802-BT	802	160	0 - 250 bar	G1/2 Radial	SS / SS
16802-BV	802	160	0 - 400 bar	G1/2 Radial	SS / SS
16802-BX	802	160	0 - 600 bar	G1/2 Radial	SS / SS

Lyth-Instrument Oy
Peltosaarencatu 8
FI-11130 Riihimäki
Finland , Europe

phone: + 358-19-760330
fax : + 358-19-722085
www.lyth.fi